Schedule A

- l Jamsion Mark II manually operated horizontal sliding cooler door, 8'0" x 10'0". Insulation 2" foamed in place polyurethane. Metal clad door & exposed frame clad full het #26 gauge galvanized steel door to slide to right hand side to open.
- 5 special series "50" banana room doors hinged left w/safety release feature on latch
- 2 Mark II bi-part electroglide doors 8'0" x 9'0", 2" insulation, safety release feature
- l Mark II electroglide freezer door 8'0" x 9'0" 4" insulation, safety release feature
- 4 Mark II, manually operated vertical sliding cooler doors, 2" insulation, 7'0" x 9'0" $\,$
- 2 Mark II, manually operated vertical sliding cooler doors, 2" insulation, 8.0" x 10.0" $\,$
- 3 Nieco Model R-6014 60" air screens
- 3 Nieco model R-3614 36" air screens
- 4 McGuire foamed pad door seals 7'0" x 9'0"
- 2 McGuire rail dock shelters 10'9" x 12'0"
- 2 #4119 Toastmaster char broilers
- 1 # 1410 Duro Speed Fan
- l Baker Model FTD-040 #57222 48 volt electric forklift complete w/ battery and charger
- 1 Clark Battery Powered Fork Lift Truck, model NST30, 3000 lbs. capacity at 24 load center, together with 201" Full Free Lift Triple Stage Upright; 42" Forks; 48" Load Back Rest; Driver's Overhead Guard; Cold Storage Processing with heaters; Hobbs Hour Meter; Battery Discharge Indicator; Polyurethane Caster & Load Wheels; Gould, model 12-145X-13 Battery, 870 APH; Gould, model GSP12-960-1 Charger.
- l Langsenkamp, model 6060DMTS, 4" Guard Rails, 8"Stops; Crimped 16" from truck end; Chain Lifts; 8" height differential
- Office Furniture for Bi-Lo, Inc. Warehouse including 3 # CR2676 Credenza; 3 #CF 2676 Desks

Release Recorded Feb. 3, 1969 at 9:52 A. M., #18269.

